

**No. VBD
VENTILATION & BLOWER DUCT**



Part Number	Inside Diameter	Bend Radius	Compression Ratio	Max. Neg. Pressure In. Hg	Max. Pos. Pressure PSI
VBD-400	4"	2-1/2"	10:1	9	2
VBD-500	5"	3-1/8"	10:1	5	1.9
VBD-600	6"	3-1/2"	10:1	5	1.85
VBD-800	8"	4-3/4"	10:1	6	1.7
VBD-1000	10"	6"	10:1	3.2	1.67
VBD-1200	12"	7"	10:1	1.84	1.2
VBD-1400	14"	8-1/4"	10:1	1.2	1
VBD-1600	16"	9-1/2"	10:1	.78	.8
VBD-1800	18"	10-1/4"	10:1	.55	.5
VBD-2000	20"	11-1/2"	10:1	.4	.5
VBD-2200	22"	12"	10:1	.3	.45
VBD-2400	24"	14"	10:1	.23	.3

Single-ply polyester reinforced PVC vinyl fabric hose construction with an external wearstrip reinforced with a spring steel wire helix. Features include: highly compressible, lightweight, retractability allows for convenient storage and easy transport in a fraction of its fully extended length, low friction loss, wearstrip offers external abrasion resistance. Flame retardant to UL-94VO. Recommended for air movement applications.

Available Sizes: 4" - 48" I.D.
Temperature Range: -20°F to 180°F
Stock Length: 25'