

### No. 320 - GRAPHITED BRAIDED PACKING



Larger sizes available on request.

**Description:** Interlock braided using long, white chrysolite fibers which are impregnated with a petroleum-based oil and graphite compound. After braiding, the surface is graphited.

**Applications:** A good general service packing that ensures an excellent seal against brine, contaminated hot and cold water, saturated steam, oils, solvents and weak acids. Recommended for use in centrifugal and rotary pumps and low pressure valve stems.

Part #	Size	Ft/Lb.	ISSA #
320-140	1/4"	26.0	810183
320-516	5/16"	17.0	810184
320-380	3/8"	12.5	810185
320-716	7/16"	8.2	810186
320-120	1/2"	6.6	810187
320-916	9/16"	5.6	810188
320-580	5/8"	4.5	810189
320-340	3/4"	3.1	810191
320-780	7/8"	2.3	810193
320-100	1"	1.8	810194

**Temperature Limit:** to 500°F.

**pH Range:** 4-10.

**Shaft Speed:** to 2000 FPM.

**Non-Stock, Special Order.**

### No. 325 - GRAPHITED BRAIDED PACKING



Larger sizes available on request.

**Description:** Square braided using long, white chrysolite fibers which are impregnated yarn-by-yarn with a petroleum-based oil and graphite compound. After braiding, the surface is graphited.

**Applications:** A good general service packing that ensures an excellent seal against hot or cold water, saturated steam, petroleum, caustic solutions and weak acids. Recommended for use in centrifugal and rotary pumps and low pressure valve stems.

Part #	Size	Ft/Lb.	ISSA #
325-180	1/8"	114.0	810241
325-316	3/16"	48.0	810242
325-140	1/4"	22.0	810243
325-516	5/16"	17.0	810244
325-380	3/8"	11.0	810245
325-716	7/16"	8.6	810246
325-120	1/2"	6.8	810247
325-916	9/16"	5.3	810248
325-580	5/8"	4.0	810249
325-340	3/4"	3.0	810251
325-780	7/8"	1.8	810253
325-100	1'	1.6	810255
325-118	1-1/8"	1.4	--
325-114	1-1/4"	1.3	--
325-112	1-1/2"	1.1	--

**Temperature Limit:** to 500°F.

**pH Range:** 4-10.

**Shaft Speed:** to 2000 FPM.

**Non-Stock, Special Order.**